



SPECIAL FLOORS

PRODUCT DESCRIPTION

WOODGUARD SPECIAL FLOORS is a one component product offering protection against soiling, all types of stains, plus the main causes of deterioration such as atmospheric pollution, grease-based stains, penetration of liquids and giving protection against water, oil and graffiti penetration to wooden floors.

WOODGUARD SPECIAL FLOORS will also make maintenance easier and ensures wood has a prolonged life.

WOODGUARD SPECIAL FLOORS is a wood preservative that respects the characteristics of the wood it's applied to (grain etc). It is not film-forming and the treated surface remains permeable to both air and water vapour.

WOODGUARD SPECIAL FLOORS may be used on any wood surface that you wish to preserve in its natural state (teak, pine, exotic woods, oak...). Except for painted, varnished or preservative-treated wood.

Environmentally user friendly	Water repellence	Water proofing properties	Oil repellence	Anti staining performance	Anti graffiti protection	Weak acid resistance	Resistance to abrasion	Colour enhancer	Colour	UV resistance
• VOC = < 4g/L	•		•	•			•			•

CERTIFICATIONS

- **LRVision laboratory:** WOODGUARD SPECIAL FLOORS proved to have efficient water and oil repellence properties.

And much more...

Test reports are available upon request at information@guardindustrie.com

ADVANTAGES AND CHARACTERISTICS

- Can be applied to vertical and horizontal surfaces, both inside and outside
- Prevents the penetration of water and oily liquids
- Anti-staining, anti-dirt. Stops build up of dirt due to pollution.
- Makes cleaning easier
- Allows the surface to breathe
- Non-hazardous and non-toxic
- Water-borne product
- Solvent and silicone-free
- Biodegradable > 95% according to OECD standards
- UV-resistant, does not discolour
- Ready and easy to use
- Non-flammable
- One component

TOOLS



+



Brush

AND/OR



Roller

OR



HVLP spray
(High Volume
Low Pressure)

APPLICATION OF THE PRODUCT



On certain types of oak and walnut, the product might cause black stains because of its water content. We recommend wearing gloves, safety goggles and an adequate combination during the period of use. **A trial should always first be tested on a small area to confirm the products suitability for the surface being treated.**

1) Surface preparation

Surface has to be clean, dust-free and dry. Remove organic growth, stains and marks of atmospheric pollution before applying the product. To see which product of our cleaners range you should use, please refer to page 4.

2) Application of the product



Use the product neat, do not dilute or mix with any other product. **Do not forget to shake the container before application.**



Apply the product to saturation point with either:
- Brush (2 to 3 applications. In the event of brush marks, homogenize with a roller.)
- Roller (2 to 3 applications)
- HVLP spray (2 to 4 crossed applications.)



Drying time between each application: 15 minutes.



Do not over apply the product; remove any excess with a roller.



For more efficiency, rub down the surface after the first layer.



Allow the surface to dry for 48 hours. Protect the surface for 24 hours from rain and dust. For the optimum performance wait 5 for 7 days.

GENERAL INFORMATION

➤ Product performance

- After 2 days: Achieves water repellent property
- After 4 days: Achieves oil repellent property
- After 7 days: Achieves optimum performance

➤ Coverage

Coverage depends on a material's porosity. These figures are approximate and should be used as a general guideline:

8 – 12 m² / litre for two applications

➤ Storage

Lifespan: 12 months

Keep in a cool, dry place, away from extreme cold; do not store in temperatures < 5°C

➤ Packaging

1, 5; 10 litre containers

CASE STUDY



Wooden floors are subjected to natural and human attacks like water impregnation, UV rays which make the wood turning grey, micro organisms, stains and foot traffic. To avoid these problems, a parquet manufacturer decided to treat his wooden floors with WoodGuard for Floors.